2360 Fifth Street Mandeville, LA 70471 (985) 629-2082 Phone (985) 629-2110 Fax

HOSE AND PIPELINE TESTS

| VESSEL: | FMT 1410 | |
|---|--|--|
| THE FOLLOWING ITEMS HAVE BEEN CHECKED AND TESTED IN ACCORDANCE WITH 46CFR 35.35-70 AND 33CFR 156.170 ON | | |
| | PRESSURE GAUGES HAVE BEEN CHECKED WITHIN 10% OF ACCURACY. | |
| | EMERGENCY SHUTDOWN HAS BEEN CHECKED AND FOUND OPERABLE. | |
| | TRASFER SYSTEM RELIEF VALVE HAS BEEN TESTED AND CHECKED - 125 P.S.I. | |
| NA | ALL TRANSFER PIPING SYSTEMS AND ASSOCIATED VALVES HAVE BEEN TESTED AND CHECKED AT 187.5 P.S.I. | |
| | CARGO HOSE VISUALLY AND HYDROSTATICALLY CHECKED TO 225 P.S.I. | |
| THE ABOVE ITEMS CHECKED, TEST | PED AND VERTETED BY: | |
| THE ADOVE TIENS CHECKED, TED. | Stan Site | |

Florida Marine Transporters Inc.

MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BB-NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER OPERATIONS SECTION 61.00-61.306

| Olladia on | | |
|--|--|--|
| VESSEL: FINT 1410 | OFFICIAL NUMBER: 1299465 | |
| TESTING LOCATION: CARLINE FUT | MAXIMUM LOADING RATE (BPH) 4285 | |
| - A11 | PRESSURE INDICATOR: MANOMETER | |
| 11211(0) 122.121 | a receipt of management | |
| VESSEL OWNER AND ADDRESS: FMT 2360 FIFTH ST. MANDENIUS | | |
| TEST RESULTS | | |
| TEST DATE: 2-7-24 | 1, 21, 42 | |
| 12" 25 140 | 1/00 | |
| BEGINNING PRESSURE: 28" of 42 ° | REGINNING TIME: | |
| ENDING PRESSURE: 28"0F H20 | ENDING TIME: //30 | |
| ENDERG LIGORAGE | 5.2 02/420 | |
| TOTAL PRESSURE LOSS: | ALLOWABLE PRESSURE LOSS: | |
| VICTOR IS CONSTITUTED VAPOR TIGHT IF TOT | AL PRESSURE LOSS" IS LESS THAN "ALLOWABLE PRESSURE LOSS" | |
| NOTE: VESSEL IS CONSIDERED (72 92 AND | COCCUPATION (4 20/E: ANTELIC | |
| THIS VESSEL HAS BEEN TESTED IN A | CCORDANCE WITH SECTION 61.304F, AND IS | |
| CONSIDERED VAPOR TIGHT. | | |
| CL 101 | WITNESS: Chad To //iver (PRINT) | |
| TESTER: STUNISH (PRINT) | WITNESS: | |
| (SIGN) | WITNESS: LOOVICE (SIGN) | |
| TESTER: (BION) | FINT | |
| | | |
| 2007 | AFFILIATION OF WITNESS | |
| CALCULATION OF ALLOWABLE PRESSURE LOSS: | | |
| 0861 x 18.7 x (4285 / 1/, | 066)= 5.2 | |
| 0.861 x 15.7 x (4285 / 1/, | V) (APL) | |
| | | |
| TP = 14.7 Plus the Barge test pressure in PSI ($L = MAXIMUM$ LOADING RATE IN BARRELS PER H | ipsi – 10 balica) DUR | |
| Y = YOLUME OF TANK(S) IN BARRELS | | |
| APL = ALLOWABLE PRESSURE LOSS IN INCHES OF | WATER | |
| NOTES: 14.70psi = 406.8 inches of H2O | | |
| 1psi = 27.67 inches of H2O | | |
| 1 inch = 25.40 mm | | |
| finch = 2.54 cm foz. = 1.729 inches OF H2O | | |
| | | |