2360 Fifth Street Mandeville, LA 70471 (985) 629-2082 Phone (985) 629-2110 Fax

HOSE AND PIPELINE TESTS

· ·	
VESSEL:	FMT 3168
THE FOLLOWING ITEMS HAVE BEEN CHECKED AND TESTED IN ACCORDANCE WITH 46CFR 35.35-70 AND 33CFR 156.170 ON 7-17-23	
	PRESSURE GAUGES HAVE BEEN CHECKED WITHIN 10% OF ACCURACY. EMERGENCY SHUTDOWN HAS BEEN CHECKED AND FOUND OPERABLE.
NIA	TRASFER SYSTEM RELIEF VALVE HAS BEEN TESTED AND CHECKED - 125 P.S.I. ALL TRANSFER PIPING SYSTEMS AND ASSOCIATED VALVES HAVE BEEN TESTED AND CHECKED AT 187.5 P.S.I.
THE ABOVE ITEMS CHECKED, TEST	ED AND VERIFIED BY:

Florida Marine Transporters Inc.

MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BB-NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER OPERATIONS SECTION 61.00-61.306 FMT 3168 OFFICIAL NUMBER:_ TESTING LOCATION: LNTER GULF FLT MAXIMUM LOADING RATE (BPH) PRESSURE INDICATOR: TANK(S) TESTED: _ VESSEL OWNER AND ADDRESS: FLORIDA MARINE TEST RESULTS 7-17-23 TEST DATE: BEGINNING PRESSURE: BEGINNING TIME: ENDING TIME: ENDING PRESSURE: TOTAL PRESSURE LOSS: NOTE: VESSEL IS CONSIDERED VAPOR TIGHT IF "TOTAL PRESSURE LOSS" IS LESS THAN "ALLOWABLE PRESSURE LOSS" THIS VESSEL HAS BEEN TESTED IN ACCORDANCE WITH SECTION 61.304F, AND IS CONSIDERED VAPOR TIGHT. WITNESS: (PRINT) (SIGN) AFFILIATION OF WITNESS CALCULATION OF ALLOWABLE PRESSURE LOSS: TP = 14.7 PLUS THE BARGE TEST PRESSURE IN PSI (1psi = 16 ounces) L = MAXIMUM LOADING RATE IN BARRELS PER HOUR

APL = ALLOWABLE PRESSURE LOSS IN INCHES OF WATER

NOTES:

i4.70p9i = 406.8 inches of H2O

lpsi = 27.67 inches of H2O

l inch = 25.40 mm

linch = 2.54 cm

loz = 1.729 inches OF H2O

V = VOLUME OF TANK(S) IN BARRELS