2360 Fifth Street Mandeville, LA 70471 (985) 629-2082 Phone (985) 629-2110 Fax

HOSE AND PIPELINE TESTS

VESSEL:	-MT 6014
THE FOLLOWING ITEMS HAVE BEEN 46CFR 35.35-70 AND 33CFR 156.	CHECKED AND TESTED IN ACCORDANCE WITH 170 ON $12-6-23$.
	PRESSURE GAUGES HAVE BEEN CHECKED WITHIN 10% OF ACCURACY.
	EMERGENCY SHUTDOWN HAS BEEN CHECKED AND FOUND OPERABLE.
	TRASFER SYSTEM RELIEF VALVE HAS BEEN TESTED AND CHECKED - 125 P.S.I.
1 /	ALL TRANSFER PIPING SYSTEMS AND ASSOCIATED VALVES HAVE BEEN TESTED AND CHECKED AT 187.5 P.S.I.
~/A	CARGO HOSE VISUALLY AND HYDROSTATICALLY CHECKED TO 225 P.S.I.
THE ABOVE ITEMS CHECKED, TESTED AND VERIFIED BY:	
B = 2	

linch = 2.54 cm

loz. = 1.729 inches OF H2O

Florida Marine Transporters Inc.

MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BB-NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER OPERATIONS SECTION 61,00-61.306 FMT 6014 OFFICIAL NUMBER: 1256649 TESTING LOCATION: CATES FLT MAXIMUM LOADING RATE (BPH) 5,000 PRESSURE INDICATOR: MANOMETER VESSEL OWNER AND ADDRESS: FLORIDA MARINE 2860 FIFTH ST. TEST RESULTS TEST DATE: 12-6-23 BEGINNING TIME: 1400 BEGINNING PRESSURE: 28" OF 420 ENDING PRESSURE: __ 28" OF #20 ENDINGTIME: 1430 TOTAL PRESSURE LOSS: ____ ALLOWABLE PRESSURE LOSS: 2.2" . Hao NOTE: VESSEL IS CONSIDERED VAPOR TIGHT IF "TOTAL PRESSURE LOSS" IS LESS THAN "ALLOWABLE PRESSURE LOSS" THIS VESSEL HAS BEEN TESTED IN ACCORDANCE WITH SECTION 61.304F, AND IS CONSIDERED VAPOR TIGHT. MATT BRAZZEL (PRINT) WITNESS: __ (PRINT) (SIGN) (SIGN) AFFILIATION OF WITNESS CALCULATION OF ALLOWABLE PRESSURE LOSS: TP = 14.7 PLUS THE BARGE TEST PRESSURE IN PSI (1psi = 16 ounces) L = MAXIMUM LOADING RATE IN BARRELS PER HOUR V = VOLUME OF TANK(S) IN BARRELS APL = ALLOWABLE PRESSURE LOSS IN INCHES OF WATER NOTES: 14.70 psi = 406.8 inches of H2O1psi = 27.67 inches of H2O 1 inch = 25.40 mm