

Florida Marine Transporters, Inc.

2360 Fifth Street Mandeville, LA 70471 (985) 629-2082 Phone (985) 629-2110 Fax

HOSE AND PIPELINE TESTS

VESSEL:_	FMT 1078
THE FOLLOWING ITEMS CFR 35.35-70 AND 33 CI	FR 156.170 ON 3-13-13
	_PRESSURE GAUGES HAVE BEEN CHECKED WITHIN 10% OF ACCURACY.
	_EMERGENCY SHUTDOWN HAS BEEN CHECKED AND FOUND OPERABLE.
	TRANSFER SYSTEM RELIEF VALVE HAS BEEN TESTED AND CHECKED - 125 P.S.I
	_ALL TRANSFER PIPING SYSTEMS AND ASSOCIATED VALVES HAVE BEEN TESTED AND CHECKED AT 187.5 P.S.I.
N/A	_CARGO HOSE VISUALLY AND HYDROSTATICALLY CHECKED TO 225 P.S.I.
V	_VAPOR PIPELINE HAS BEEN VISUALLY CHECKED AND IS CLEAR OF POLMERIZING CARGO.
THE ABO	VE ITEMS CHECKED, TESTED, AND VERIFIED BY:

Florida Marine Transporters Inc.

MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BB-NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER OPERATIONS SECTION 61.00-61.306

VESSEL: FMT 1078 OF	FICIAL NUMBER: 1283414
TESTING LOCATION: FMT Shipyard MA	XIMUM LOADING RATE (BPH) 4, 285
	ESSURE INDICATOR: MANOMETER
VESSEL OWNER AND ADDRESS: FLORIDA MARIN	E 2360 FIFTH ST- MANDEVILLE WA
	ESULTS
BEGINNING PRESSURE: 28" of 42 ° BEG	GINNING TIME: 10'.00
ENDING PRESSURE: 28" of H20 EN	DING TIME: 11:00
TOTAL PRESSURE LOSS:O AL	LOWABLE PRESSURE LOSS: 4,90 0/2/420
NOTE: VESSEL IS CONSIDERED VAPOR TIGHT IF "TOTAL PR	ESSURE LOSS" IS LESS THAN "ALLOWABLE PRESSURE LOSS"
TESTER: (PRINT) WI	VAPOR TIGHT. TINESS: Adam Bravd (PRINT) TINESS: (SIGN) FMT FILLATION OF WITNESS
CALCULATION OF ALLOWABLE PRESSURE LOSS:	
0.861 x 14.7 x (4,285 / 1/,066 (V)	(APL)
TP = 14.7 PLUS THE BARGE TEST PRESSURE IN PSI (1psi = L = MAXIMUM LOADING RATE IN BARRELS PER HOUR V = VOLUME OF TANK(S) IN BARRELS APL = ALLOWABLE PRESSURE LOSS IN INCHES OF WATE NOTES: 14.70psi = 406.8 inches of H2O	
NOTES: 14.70psi = 406.8 inches of H2O 1psi = 27.67 inches of H2O 1 inch = 25.40 mm 1inch = 2.54 cm 1oz. = 1.729 inches OF H2O	