2360 Fifth Street Mandeville, LA 70471 (985) 629-2082 Phone (985) 629-2110 Fax

HOSE AND PIPELINE TESTS

w *	vessel: ///	7 3015	
THE FOLLOWING ITEMS HAVE BEEN CHECKED AND TESTED IN ACCORDANCE WITH 46CFR 35.35-70 AND 33CFR 156.170 ON			
_		PRESSURE GAUGES HAVE BEEN CHECKED WITHIN 10% OF ACCURACY.	
।।। २०		EMERGENCY SHUTDOWN HAS BEEN CHECKED AND FOUND OPERABLE.	
e		TRASFER SYSTEM RELIEF VALVE HAS BEEN TESTED AND CHECKED - 125 P.S.I.	
,		ALL TRANSFER PIPING SYSTEMS AND ASSOCIATED VALVES HAVE BEEN TESTED AND CHECKED AT 187.5 P.S.I.	
_	NA	CARGO HOSE VISUALLY AND HYDROSTATICALLY CHECKED TO 225 P.S.I.	
THE ABOVE IT	EMS CHECKED, TEST	ED AND VERIFIED BY:	

loz. = 1.729 inches OF H2O

Florida Marine Transporters Inc.

MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

VT	STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER IS SECTION 61.00-61.306
VESSEL: MT 3015	OFFICIAL NUMBER: 1/00046
TESTING LOCATION: Gates Fleet	
TANK(S) TESTED: ALL	PRESSURE INDICATOR: MANOMETER
VESSEL OWNER AND ADDRESS: FLORIDA MA	RINE 2860 FIFTH ST. WANDEULIE CH
TEST DATE: 9/11/23	T RESULTS
BEGINNING PRESSURE: 28" of 42°	BEGINNING TIME: /OO
ENDING PRESSURE: 1804 Had	ENDING TIME:
TOTAL PRESSURE LOSS:	ALLOWABLE PRESSURE LOSS: 2.2" A H20
NOTE: VESSEL IS CONSIDERED YAPOR TIGHT IF "TOT	AL PRESSURE LOSS" IS LESS THAN "ALLOWABLE PRESSURE LOSS"
	CCORDANCE WITH SECTION 61.304F, AND IS ED VAPOR TIGHT.
TESTER: MATT BRAZZEC (PRINT) TESTER: (SIGN)	1 Ch
CALCULATION OF ALLOWABLE PRESSURE LOSS:	AFFILIATION OF WITNESS
8	
$0.861 \times 15.7 \times 5000 \times 30$	$\frac{7^{6}\mathcal{E}}{(APL)} = \frac{\mathcal{Z}}{(APL)}$
TP = 14.7 PLUS THE BARGE TEST PRESSURE IN PSI (1) L = MAXIMUM LOADING RATE IN BARRELS PER HO V = VOLUME OF TANK(S) IN BARRELS APL = ALLOWABLE PRESSURE LOSS IN INCHES OF W	DUR
NOTES: 14.70psi = 406.8 inches of H2O	
1psi = 27.67 inches of H2O 1 inch = 25.40 mm linch = 2.54 cm	