2360 Fifth Street Mandeville, LA 70471 (985) 629-2082 Phone (985) 629-2110 Fax

HOSE AND PIPELINE TESTS

vessel:	EMET 3021	
	¥ 4.	
THE FOLLOWING ITEMS HAVE BEEN CHECKED AND TESTED IN ACCORDANCE WITH 46CFR 35.35-70 AND 33CFR 156.170 ON 4-16-25		
	PRESSURE GAUGES HAVE BEEN CHECKED WITHIN 10% OF ACCURACY.	
	EMERGENCY SHUTDOWN HAS BEEN CHECKED AND FOUND OPERABLE.	
	TRASFER SYSTEM RELIEF VALVE HAS BEEN TESTED AND CHECKED - 125, P.S.I.	
w/A	ALL TRANSFER PIPING SYSTEMS AND ASSOCIATED VALVES HAVE BEEN TESTED AND CHECKED AT 187.5 P.S.I.	
	CARGO HOSE VISUALLY AND HYDROSTATICALLY CHECKED TO 225 P.S.I.	
THEMS OFFICED TREMS	ED AND VERZETED BY:	

Florida Marine Transporters Inc.

MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BB-NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER OPERATIONS SECTION 61.00-61.306

VESSEL: FWT BOZI	OFFICIAL NUMBER: 11088 16
TESTING LOCATION: WIRIDE FLT	MAXIMUM LOADING RATE (BPH) 5,000
TANK(S) TESTED: ALL	PRESSURE INDICATOR: MANOMETER
VESSEL OWNER AND ADDRESS: FMT 230	60 FIFTH ST. MANDEVICE
TEST DATE: 4-16-25	RESULTS
BEGINNING PRESSURE: 28" of 42°	BEGINNING TIME: 1430
ENDING PRESSURE: 22 "OF HAO	
TOTAL PRESSURE LOSS:O	
THIS VESSEL HAS BEEN TESTED IN AC	CORDANCE WITH SECTION 61.304F, AND IS D VAPOR TIGHT.
TESTER: TARRED GOIN (PRINT) TESTER: (SIGN)	WITNESS: D. J. GOIN. (PRINT) WITNESS: (SIGN) AFFILIATION OF WITNESS
CALCULATION OF ALLOWABLE PRESSURE LOSS:	AFFILIATION OF WITHESS
0.861 x 15.7 x $(5,000)$ (7) (L) (V)	$\frac{206}{(APL)} = \frac{2.2}{(APL)}$
TP = 14.7 PLUS THE BARGE TEST PRESSURE IN PSI (II L = MAXIMUM LOADING RATE IN BARRELS PER HOW V = VOLUME OF TANK(S) IN BARRELS APL = ALLOWABLE PRESSURE LOSS IN INCHES OF WORLD INCHES OF WORLD INCHES OF H2O 1 psi = 27.67 inches of H2O 1 inch = 25.40 mm 1 inch = 2.54 cm 1 oz. = 1.729 inches OF H2O	OUR