

2360 Fifth Street Mandeville, LA 70471 (985) 629-2082 Phone (985) 629-2110 Fax

## HOSE AND PIPELINE TESTS

| vessel:F  | MT 3023   |
|---|---|
| 20 E)   |   |
| THE FOLLOWING ITEMS HAVE BEEN 46CFR 35.35-70 AND 33CFR 156. | CHECKED AND TESTED IN ACCORDANCE WITH 170 ON 6-6-23.  |
|   | PRESSURE GAUGES HAVE BEEN CHECKED WITHIN 10% OF ACCURACY.   |
|   | EMERGENCY SHUTDOWN HAS BEEN CHECKED AND FOUND OPERABLE.   |
|   | TRASFER SYSTEM RELIEF VALVE HAS BEEN TESTED AND CHECKED - 125, P.S.I. ALL TRANSFER PIPING SYSTEMS AND |
| N/A   | ASSOCIATED VALVES HAVE BEEN TESTED AND CHECKED AT 187.5 P.S.I.  |
| V- 1/1  | CARGO HOSE VISUALLY AND HYDROSTATICALLY CHECKED TO 225 P.S.I.   |
| THE ABOVE ITEMS CHECKED, TESTE                              | ED AND VERIFIED BY:   |
|   |   |

loz. = 1.729 inches OF H2O

Florida Marine Transporters Inc.

## MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BB-NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER OPERATIONS SECTION 61.00-61.306 FMT 3023 OFFICIAL NUMBER: 1108817 TESTING LOCATION: DEUALL FLT MAXIMUM LOADING RATE (BPH) 5,000 TANK(S) TESTED: ALL PRESSURE INDICATOR: MANOMETER VESSEL OWNER AND ADDRESS: FLORIDA MARINE 2860 FIFTH ST. MANDENLIE CA TEST RESULTS TEST DATE: 6-6-23 BEGINNING PRESSURE: 28" 00 H2 0 BEGINNING TIME: 1300 ENDING PRESSURE: 28" OF H20 TOTAL PRESSURE LOSS: \_\_\_\_\_\_ ALLOWABLE PRESSURE LOSS: 2. 2 . H20 NOTE: VESSEL IS CONSIDERED VAPOR TIGHT IF "TOTAL PRESSURE LOSS" IS LESS THAN "ALLOWABLE PRESSURE LOSS" THIS VESSEL HAS BEEN TESTED IN ACCORDANCE WITH SECTION 61.304F, AND IS CONSIDERED VAPOR TIGHT. MATT BRAZZEL (PRINT) WITNESS:\_ \_\_\_(SIGN) AFFILIATION OF WITNESS CALCULATION OF ALLOWABLE PRESSURE LOSS: TP = 14.7 PLUS THE BARGE TEST PRESSURE IN PSI (1psi = 16 ounces) L = MAXIMUM LOADING RATE IN BARRELS PER HOUR V = VOLUME OF TANK(S) IN BARRELS APL = ALLOWABLE PRESSURE LOSS IN INCHES OF WATER NOTES 14.70 psi = 406.8 inches of H2O1psi = 27.67 inches of H2O 1 inch = 25.40 mmlinch = 2.54 cm