2360 Fifth Street Mandeville, LA 70471 (985) 629-2082 Phone (985) 629-2110 Fax

HOSE AND PIPELINE TESTS

VESSEL:	FMT 3043	
123. 21	200	
THE FOLLOWING ITEMS HAVE BEEN CHECKED AND TESTED IN ACCORDANCE WITH 46CFR 35.35-70 AND 33CFR 156.170 ON		
	PRESSURE GAUGES HAVE BEEN CHECKED WITHIN 10% OF ACCURACY.	
	EMERGENCY SHUTDOWN HAS BEEN CHECKED AND FOUND OPERABLE.	
	TRASFER SYSTEM RELIEF VALVE HAS BEEN TESTED AND CHECKED - 125 P.S.I.	
	ALL TRANSFER PIPING SYSTEMS AND ASSOCIATED VALVES HAVE BEEN TESTED AND CHECKED AT 187.5 P.S.I.	
	CARGO HOSE VISUALLY AND HYDROSTATICALLY CHECKED TO 225 P.S.I.	
e.		
THE ABOVE ITEMS CHECKED, TEST	FED AND VERIFIED BY:	
THE ADOVE TIERS CHICAGO, AND	1-11-	

Florida Marine Transporters Inc.

MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BB-NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER OPERATIONS SECTION 61.00-61.306

VESSEL: FMT 3043	OFFICIAL NUMBER: 1123 577
TESTING LOCATION: PRICE UACHERIE	MAXIMUM LOADING RATE (BPH) 5,000
TANK(S) TESTED: ALL VESSEL OWNER AND ADDRESS: FMT 236	PRESSURE INDICATOR: MANOMETER
VESSEL OWNER AND ADDRESS: FmT 236	OFIFTH ST. MANDEVILLE
	RESULTS
TEST DATE: 10-15-23	*
	BEGINNING TIME: 1300
BEGINNING PRESSURE: 28" of 42° ENDING PRESSURE: 22'01=142°	ENDING TIME:
TOTAL PRESSURE LOSS:	
NOTE: VESSEL IS CONSIDERED VAPOR TIGHT IF "TOT.	AL PRESSURE LOSS" IS LESS THAN "ALLOWABLE PRESSURE LOSS"
	CCORDANCE WITH SECTION 61.304F, AND IS ED VAPOR TIGHT.
TESTER: CARPY HILL (PRINT)	WITNESS: Stevasiles (PRINT)
TESTER: CARPY HIC (PRINT) TESTER: (SIGN)	WITNESS: (SIGN)
	FMT
CALCULATION OF ALLOWABLE PRESSURE LOSS:	AFFILIATION OF WITNESS
CALCULATION OF ALLO WABLE PRESSURE LOSS.	
0.861 x /5.7 x (5,000 / 30,	(APL)
TP = 14.7 PLUS THE BARGE TEST PRESSURE IN PSI (1	
L = MAXIMUM LOADING RATE IN BARRELS PER H	
V = VOLUME OF TANK(S) IN BARRELS	
APL = ALLOWABLE PRESSURE LOSS IN INCHES OF V	VATER
NOTES: 14.70psi = 406.8 inches of H2O	
1psi = 27.67 inches of H2O	
1 inch = 25.40 mm	K
linch = 2.54 cm	
$1oz_{r} = 1.729$ inches OF H2O	