2360 Fifth Street Mandeville, LA 70471 (985) 629-2082 Phone (985) 629-2110 Fax

HOSE AND PIPELINE TESTS

VESSEL:	2 MT 3049
THE FOLLOWING ITEMS HAVE BEEN CHECKED AND TESTED IN ACCORDANCE WITH 46CFR 35.35-70 AND 33CFR 156.170 ON 2-1-24	
	PRESSURE GAUGES HAVE BEEN CHECKED WITHIN 10% OF ACCURACY. EMERGENCY SHUTDOWN HAS BEEN CHECKED
	AND FOUND OPERABLE. TRASFER SYSTEM RELIEF VALVE HAS BEEN TESTED AND CHECKED - 125 P.S.I.
	ALL TRANSFER PIPING SYSTEMS AND ASSOCIATED VALVES HAVE BEEN TESTED AND CHECKED AT 187.5 P.S.I.
<i>N/H</i>	CARGO HOSE VISUALLY AND HYDROSTATICALLY CHECKED TO 225 P.S.I.

THE ABOVE ITEMS CHECKED, TESTED AND VERIFIED BY:

Florida Marine Transporters Inc.

MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BB-NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER OPERATIONS SECTION 61.00-61.306

VESSEL: FMT 3049	OFFICIAL NUMBER: 1/35085
TESTING LOCATION: BUFFALO FLT	MAXIMUM LOADING RATE (BPH) 5,000
TANK(S) TESTED: ALL	PRESSURE INDICATOR: MANOMETER
VESSEL OWNER AND ADDRESS: FLORIDA MIN	RIVE 2360 FIFTH ST. MANDENUTE CH
TEST DATE: 2-1-24 TEST	RESULTS
ENDING PRESSURE: 28" OF H10	BEGINNING TIME: 1300
ENDING PRESSURE: 28" OF HID	ENDING TIME: 1330
TOTAL PRESSURE LOSS:	ALLOWABLE PRESSURE LOSS: 2.2" A H20
NOTE: VESSEL IS CONSIDERED VAPOR TIGHT IF TOTAL	L PRESSURE LOSS" IS LESS THAN "ALLOWABLE PRESSURE LOSS"
CONSIDERE	CORDANCE WITH SECTION 61.304F, AND IS ED VAPOR TIGHT. WITNESS: LEC CHAMPAGNE (PRINT) WITNESS: LC CHAMPAGNE (SIGN)
CALCULATION OF ALLOWABLE PRESSURE LOSS:	AFFILIATION OF WITNESS
0.861 x 15.7 x (5,000 / 30,7 (TP) (L) (V)	$(APL) = \frac{2 \cdot 2}{(APL)}$
IP = 14.7 PLUS THE BARGE TEST PRESSURE IN PSI (1) L = MAXIMUM LOADING RATE IN BARRELS PER HO V = VOLUME OF TANK(S) IN BARRELS APL = ALLOWABLE PRESSURE LOSS IN INCHES OF W NOTES: 14.70psi = 406.8 inches of H20	UR
NOTES: 14.70psi = 406.8 inches of H2O 1psi = 27.67 inches of H2O 1 inch = 25.40 mm 1inch = 2.54 cm 1oz. = 1.729 inches OF H2O	