2360 Fifth Street Mandeville, LA 70471 (985) 629-2082 Phone (985) 629-2110 Fax

## HOSE AND PIPELINE TESTS

FMT 3069		
THE FOLLOWING ITEMS HAVE BEEN CHECKED AND TESTED IN ACCORDANCE WITH 46CFR 35.35-70 AND 33CFR 156.170 ON		
PRESSURE GAUGES HAVE BEEN CHECKED WITHIN 10% OF ACCURACY.		
EMERGENCY SHUTDOWN HAS BEEN CHECKED AND FOUND OPERABLE.		
TRASFER SYSTEM RELIEF VALVE HAS BEEN TESTED AND CHECKED - 125 P.S.I.  ALL TRANSFER PIPING SYSTEMS AND		
ASSOCIATED VALVES HAVE BEEN TESTED AND CHECKED AT 187.5 P.S.I.		
CARGO HOSE VISUALLY AND HYDROSTATICALLY CHECKED TO 225 P.S.I.		
A Cursu Foruces		

Florida Marine Transporters Inc.

## MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BB-NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER OPERATIONS SECTION 61.00-61.306

VESSEL: FMT 3069	OFFICIAL NUMBER: 1206 879
TESTING LOCATION: GATES FLT	
TANK(S) TESTED: ALL	PRESSURE INDICATOR: MANOMETER
	PINE 2360 FIFTH ST. MANDENUTE CA
TEST DATE:	RESULTS
BEGINNING PRESSURE: 28" & H2 0	BEGINNING TIME: 1330
	ENDING TIME: 1400
TOTAL PRESSURE LOSS:	ALLOWABLE PRESSURE LOSS: 2.2". 1/20
NOTE: VESSEL IS CONSIDERED VAPOR TIGHT IF TOTAL	L PRESSURE LOSS" IS LESS THAN "ALLOWABLE PRESSURE LOSS"
THIS VESSEL HAS BEEN TESTED IN ACCORDANCE WITH SECTION 61.304F, AND IS CONSIDERED VAPOR TIGHT.	
PRINT	WITNESS: LEE CHAMPAGNE (PRINT)
PESTER: Bushu Friday (SIGN)	WITNESS: LE CHAMPAGNE (PRINT) WITNESS: Le Chyper (SIGN)
	EMP
CALCULATION OF ALLOWANT PROFESTION LOSS.	AFFILIATION OF WITNESS
CALCULATION OF ALLOWABLE PRESSURE LOSS:	
$0.861 \times 15.7 \times (5.000 / 30.3)$	$(APL) = \frac{Z \cdot Z}{(APL)}$
TP = 14.7 PLUS THE BARGE TEST PRESSURE IN PSI (IF L = MAXIMUM LOADING RATE IN BARRELS PER HO T = VOLUME OF TANK(S) IN BARRELS APL = ALLOWABLE PRESSURE LOSS IN INCHES OF W	UR
NOTES: 14.70psi = 406.8 inches of H2O	
1psi = 27.67 inches of H2O 1 inch = 25.40 mm 1inch = 2.54 cm 1 oz. = 1.729 inches OF H2O	4