

2360 Fifth Street Mandeville, LA 70471 (985) 629-2082 Phone (985) 629-2110 Fax

HOSE AND PIPELINE TESTS

	VESSEL:	FMT3074
THE FOLLOWING ITEMS HAVE BEEN CHECKED AND TESTED IN ACCORDANCE WITH 46CFR 35.35-70 AND 33CFR 156.170 ON		
ti		PRESSURE GAUGES HAVE BEEN CHECKED WITHIN 10% OF ACCURACY.
		EMERGENCY SHUTDOWN HAS BEEN CHECKED AND FOUND OPERABLE.
		TRASFER SYSTEM RELIEF VALVE HAS BEEN TESTED AND CHECKED - 125 P.S.I.
		ALL TRANSFER PIPING SYSTEMS AND ASSOCIATED VALVES HAVE BEEN TESTED AND CHECKED AT 187.5 P.S.I.
		CARGO HOSE VISUALLY AND HYDROSTATICALLY CHECKED TO 225 P.S.I.
THE ABOVE ITEMS CHECKED, TESTED AND VERIFIED BY:		

linch = 2.54 cm

1oz. = 1.729 inches OF H2O

Florida Marine Transporters Inc.

MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BB-NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER OPERATIONS SECTION 61.00-61.306 VESSEL: FMT 3074 OFFICIAL NUMBER: 11/7763 TESTING LOCATION: BLK LAKE FLT MAXIMUM LOADING RATE (BPH) 5,000 TANK(S) TESTED: ALL PRESSURE INDICATOR: MANOMETER VESSEL OWNER AND ADDRESS: FMT 2360 FI ETH ST. MANDEUK TEST RESULTS TEST DATE: 4-21-25 BEGINNING PRESSURE: 28" #200 BEGINNING TIME:____ ENDING PRESSURE: 28" OF HOO ENDING TIME: _____ ALLOWABLE PRESSURE LOSS: 2.2". H20 TOTAL PRESSURE LOSS: ____ NOTE: VESSEL IS CONSIDERED VAPOR TIGHT IF "TOTAL PRESSURE LOSS" IS LESS THAN "ALLOWABLE PRESSURE LOSS" THIS VESSEL HAS BEEN TESTED IN ACCORDANCE WITH SECTION 61.304F, AND IS CONSIDERED VAPOR TIGHT. CHAMPAGNE (PRINT) WITNESS: Davis (SIGN) ____ (SIGN) WITNESS: AFFILIATION OF WITNESS CALCULATION OF ALLOWABLE PRESSURE LOSS: $0.861 \times \frac{15.7}{\text{(TP)}} \times (\frac{5,000}{\text{(L)}}) = \frac{2.2}{\text{(APL)}}$ TP = 14.7 PLUS THE BARGE TEST PRESSURE IN PSI (1psi = 16 ounces) L = MAXIMUM LOADING RATE IN BARRELS PER HOURV = VOLUME OF TANK(S) IN BARRELS APL = ALLOWABLE PRESSURE LOSS IN INCHES OF WATER 14.70psi = 406.8 inches of H2O NOTES: 1psi = 27.67 inches of H2O 1 inch = 25.40 mm