

Florida Marine Transporters. Inc.

2360 Fifth Street Mandeville, LA 70471 (985) 629-2082 Phone (985) 629-2110 Fax

HOSE AND PIPELINE TESTS

VESSE	EL: FMT 3088
THE FOLLOWING ITI CFR 35.35-70 AND 3	EMS HAVE BEEN CHECKED AND TESTED IN ACCORDANCE WITH 46 3 CFR 156.170 ON 6-1-23
	PRESSURE GAUGES HAVE BEEN CHECKED WITHIN 10% OF ACCURACY.
	EMERGENCY SHUTDOWN HAS BEEN CHECKED AND FOUND OPERABLE.
	TRANSFER SYSTEM RELIEF VALVE HAS BEEN TESTED AND CHECKED - 125 P.S.I
	ALL TRANSFER PIPING SYSTEMS AND ASSOCIATED VALVES HAVE BEEN TESTED AND CHECKED AT 187.5 P.S.I.
NA	CARGO HOSE VISUALLY AND HYDROSTATICALLY CHECKED TO 225 P.S.I.
	VAPOR PIPELINE HAS BEEN VISUALLY CHECKED AND IS CLEAR OF POLMERIZING CARGO.
THE A	ABOVE ITEMS CHECKED, TESTED, AND VERIFIED BY:

FMT

Florida Marine Transporters, Inc.

loz. = 1.729 inches OF H2O

2360 Fifth Street Mandeville, LA 70471 (985) 629-2082 Phone (985) 629-2110 Fax

MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BE-NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER OPERATIONS SECTION 61.00-61.306 OFFICIAL NUMBER: MAXIMUM LOADING RATE (BPH). PRESSURE INDICATOR: MANOMETER Pasentine Family Enterprises LLC 2360 Fifth St. Mandeville, LA 70471 VESSEL OWNER AND ADDRESS: TEST RESULTS TEST DATE: 6-1-23 BEGINNING PRESSURE: 28 of 426 7:00 BEGINNING TIME: ENDING PRESSURE: 28" of Ha O ENDING TIME TOTAL PRESSURE LOSS: ALLOWABLE PRESSURE LOSS: 2.2 . A Mag MOYEL PASSEL IS CONSIDERED VAPOR JIGHT IF TOTAL PRESSURE LOSS" IS LESS THAN "LILOWABLE PRESSURE LOSS" THIS VESSEL WAS BEEN TESTED IN ACCORDANCE WITH SECTION 61.304F, AND IS CONSIDERED VAPOR TIGHT. PRINT WITNESS: (SIGN) WITNESS: AFFILIATION OF WITNESS CALCULATION OF ALLOWABLE PRESSURE LOSS: TP = 14.7 PLUS THE BARGE TEST PRESSURE IN PSI (1psi = 16 ounces) L = MAXIMUM LOADING RATE IN BARRELS PER HOUR v = volume of tank(s) in barrels apl = allowable pressure loss in inches of water NOTES: 14.70pst = 406.8 inches of H2O ipsi = 27.67 inches of H2O 1 inch = 25.40 mm linch = 2.54 cm