

2360 Fifth Street Mandeville, LA 70471 (985) 629-2082 Phone (985) 629-2110 Fax

## HOSE AND PIPELINE TESTS

vessel:	EMT	3092		
THE FOLLOWING ITEMS HAVE BEEN 46CFR 35.35-70 AND 33CFR 156.	CHECKEI 170 ON	) and test 12 - 29	ED IN ACCORDA	NCE WITH
	WITHIN EMERGE	1 10% OF A	OWN HAS BEEN	
	TRASFE TESTEL	R SYSTEM F AND CHECK TRANSFER	RELIEF VALVE DE RED - 125 P.S	ens and
	AND CE	HOSE	PS HAVE BEEN 187.5 P.S.I. VISUALLY CHECKED TO 22	AND

THE ABOVE ITEMS CHECKED, TESTED AND VERIFIED BY:

Florida Marine Transporters Inc.

## MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BB-NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER OPERATIONS SECTION 61.00-61.306

VESSEL: FMT 3092	OFFICIAL NUMBER: 1127956
TESTING LOCATION: LYDIA ANN FLT	MAXIMUM LOADING RATE (BPH) 5,000
TANK(S) TESTED: ALL	PRESSURE INDICATOR: MANOMETER
VESSEL OWNER AND ADDRESS: FLOR DA MA	PINE 2360 FIFTH ST. MANDEULIE CA
TEST DATE: 12-29-23	T RESULTS
BEGINNING PRESSURE: 28" 4 H2 °	BEGINNING TIME: 11 30
A . #	ENDING TIME: 1200
TOTAL PRESSURE LOSS:	ALLOWABLE PRESSURE LOSS: 2.2" A H20
NOTE: VESSEL IS CONSIDERED VAPOR TIGHT IF "TOT	AL PRESSURE LOSS" IS LESS THAN "ALLOWABLE PRESSURE LOSS"
THIS VESSEL HAS BEEN TESTED IN AC	CCORDANCE WITH SECTION 61.304F, AND IS ED VAPOR TIGHT.
TESTER: D'ANDRE FORWARD (PRINT TESTER: Budle Frank) (SIGN)	FMT
CALCULATION OF ALLOWABLE PRESSURE LOSS:	AFFILIATION OF WITNESS
0.861 x /5.7 x ( 5,000 / 30, (Y	$\frac{706}{(APL)} = \frac{2.2}{(APL)}$
TP = 14.7 PLUS THE BARGE TEST PRESSURE IN PSI (1) L = MAXIMUM LOADING RATE IN BARRELS PER HO Y = VOLUME OF TANK(S) IN BARRELS APL = ALLOWABLE PRESSURE LOSS IN INCHES OF W NOTES: 14.70psi = 406.8 inches of H2O 1 psi = 27.67 inches of H2O 1 inch = 25.40 mm 1 inch = 2.54 cm 1 oz. = 1.729 inches OF H2O	DUR