2360 Fifth Street Mandeville, LA 70471 (985) 629-2082 Phone (985) 629-2110 Fax

HOSE AND PIPELINE TESTS

	VESSEL:	17 7/34
THE FOLLOWING ITEMS HAVE BEEN CHECKED AND TESTED IN ACCORDANCE WITH 46CFR 35.35-70 AND 33CFR 156.170 ON		
		PRESSURE GAUGES HAVE BEEN CHECKED WITHIN 10% OF ACCURACY.
8 -		EMERGENCY SHUTDOWN HAS BEEN CHECKED AND FOUND OPERABLE.
· ·		TRASFER SYSTEM RELIEF VALVE HAS BEEN TESTED AND CHECKED - 125, P.S.I.
-		ALL TRANSFER PIPING SYSTEMS AND ASSOCIATED VALVES HAVE BEEN TESTED AND CHECKED AT 187.5 P.S.I.
=	1/1/	CARGO HOSE VISUALLY AND HYDROSTATICALLY CHECKED TO 225 P.S.I.

THE ABOVE ITEMS CHECKED, TESTED AND VERIFIED BY:

NOTES:

14.70 psi = 406.8 inches of H2O1 psi = 27.67 inches of H2O

1oz. = 1.729 inches OF H2O

1 inch = 25.40 mm1 inch = 2.54 cm Florida Marine Transporters Inc.

MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BB-NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER OPERATIONS SECTION 61.00-61.306 OFFICIAL NUMBER: MAXIMUM LOADING RATE (BPH) TESTING LOCATION: PRESSURE INDICATOR:__ TANK(S) TESTED: 2360 FIFTH TEST RESULTS **BEGINNING TIME:** ENDING PRESSURE ALLOWABLE PRESSURE LOSS: 2.2".x H20 TOTAL PRESSURE LOSS: THIS VESSEL HAS BEEN TESTED IN ACCORDANCE WITH SECTION 61.304F, AND IS CONSIDERED VAPOR TIGHT. JAMES (PRINT) (PRINT) WITNESS (SIGN) AFFILIATION OF WITNESS CALCULATION OF ALLOWABLE PRESSURE LOSS: TP = 14.7 PLUS THE BARGE TEST PRESSURE IN PSI (1psi = 16 ounces) L = MAXIMUM LOADING RATE IN BARRELS PER HOURV = VOLUME OF TANK(S) IN BARRELS APL = ALLOWABLE PRESSURE LOSS IN INCHES OF WATER