

2360 Fifth Street Mandeville, LA 70471 (985) 629-2082 Phone (985) 629-2110 Fax

HOSE AND PIPELINE TESTS

VESSEL:	FMT 3146
THE FOLLOWING ITEMS HAVE BEEN CHECKED AND TESTED IN ACCORDANCE WITH 46CFR 35.35-70 AND 33CFR 156.170 ON 3-9-27	
	PRESSURE GAUGES HAVE BEEN CHECKED WITHIN 10% OF ACCURACY. EMERGENCY SHUTDOWN HAS BEEN CHECKED
	AND FOUND OPERABLE. TRASFER SYSTEM RELIEF VALVE HAS BEEN TESTED AND CHECKED - 125 P.S.I.
	ALL TRANSFER PIPING SYSTEMS AND ASSOCIATED VALVES HAVE BEEN TESTED AND CHECKED AT 187.5 P.S.I. CARGO HOSE VISUALLY AND
HYDROSTATICALLY CHECKED TO 225 P.S.I. THE ABOVE ITEMS CHECKED, TESTED AND VERIFIED BY:	
1001	D'ause Foruces

Florida Marine Transporters Inc.

MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BB-NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER OPERATIONS SECTION 61.00-61.306 VESSEL: FMT 3146 OFFICIAL NUMBER: TESTING LOCATION: LYDIA ANN FCI. MAXIMUM LOADING RATE (BPH) TANK(S) TESTED: ALL PRESSURE INDICATOR: MANIONETER VESSEL OWNER AND ADDRESS: FLORIDA MARINE TEST RESULTS TEST DATE: 3-1-14 BEGINNING TIME:_ ENDING PRESSURE: TOTAL PRESSURE LOSS: NOTE: VESSEL IS CONSIDERED VAPOR TIGHT IF "TOTAL PRESSURE LOSS" IS LESS THAN "ALLOWABLE PRESSURE LOSS" THIS VESSEL HAS BEEN TESTED IN ACCORDANCE WITH SECTION 61.304F, AND IS CONSIDERED VAPOR TIGHT. WITNESS: __ AFFILIATION OF WITNESS CALCULATION OF ALLOWABLE PRESSURE LOSS: (15.7) × (4,285) (10,066) = (5.2) (17) (17)TP = 14.7 PLUS THE BARGE TEST PRESSURE IN PSI (1psi = 16 ounces) L = MAXIMUM LOADING RATE IN BARRELS PER HOUR V = VOLUME OF TANK(S) IN BARRELS APL = ALLOWABLE PRESSURE LOSS IN INCHES OF WATER 14.70psi = 406.8 inches of H2O NOTES: lpsi = 27.67 inches of H2O i inch = 25.40 mm linch = 2.54 cm102. = 1.729 inches OF HZO