

2360 Fifth Street Mandeville, LA 70471 (985) 629-2082 Phone (985) 629-2110 Fax

HOSE AND PIPELINE TESTS

VESSEL:	FMT3158
THE FOLLOWING ITEMS HAVE BEEN 46CFR 35.35-70 AND 33CFR 156.	CHECKED AND TESTED IN ACCORDANCE WITH 170 ON
	PRESSURE GAUGES HAVE BEEN CHECKED WITHIN 10% OF ACCURACY.
	EMERGENCY SHUPDOWN HAS BEEN CHECKED AND FOUND OPERABLE.
	TRASFER SYSTEM RELIEF VALVE HAS BEEN TESTED AND CHECKED - 125 P.S.I.
. 2 /	ALL TRANSFER PIPING SYSTEMS AND ASSOCIATED VALVES HAVE BEEN TESTED AND CHECKED AT 187.5 P.S.I.
N/A	CARGO HOSE VISUALLY AND HYDROSTATICALLY CHECKED TO 225 P.S.I.
THE ABOVE ITEMS CHECKED, TESTI	ED AND VERIFIED BY:

2360 Fifth Street Mandeville, LA 7:347' Phone (985) 529-2082 Fax (985) 529-2120

Florida Marine	
Transporters Inc.	
11001	

MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BB-NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER OPERATIONS SECTION 61.00-61.306 VESSEL: FMT 3158 OFFICIAL NUMBER: 1170149 TESTING LOCATION: BUTF FLT TV CTY MAXIMUM LOADING RATE (BPH) 5,000 TANK(S) TESTED: ALL PRESSURE INDICATOR: MANAGEMENT VESSEL OWNER AND ADDRESS: FLORIDA MARINE 2360 FIFTH ST. MANDEVILLE TEST RESULTS TEST DATE: 10-4-23 BEGINNING PRESSURE: 28" OF H2 0

ENDING PRESSURE: 28" OF H2 0

ENDING TIME: /330 ALLOWABLE PRESSURE LOSS: 2.2" ... H20 NOTE: VESSEL IS CONSIDERED VAPOR LIGHT IF TOTAL PRESSURE LOSS" IS LESS THAN "ALLOWABLE PRESSURE LOSS" THIS VESSEL HAS BEEN TESTED IN ACCORDANCE WITH SECTION 61.304F, AND IS CONSIDERED VAPOR TIGHT. (SIGN) WITNESS: AFFILIATION OF WITNESS CALCULATION OF ALLOWABLE PRESSURE LOSS: $0.861 \times 15.7 \times (5,000) = 2.2$ (TP) (L) (V) (APL) TP = 14.7 PLUS THE BARGE TEST PRESSURE IN PSI (1psi = 16 ounces) L = MAXIMUM LOADING RATE IN BARRELS PER HOUR V = VOLUME OF TANK(S) IN BARRELS APL = ALLOWABLE PRESSURE LOSS IN INCHES OF WATER 14.70psi = 406.8 inches of H2O NOTES: 1psi = 27.67 inches of H2O 1 inch = 25.40 mmlinch = 2.54 cm1oz. = 1.729 inches OF H2O