

2360 Fifth Street Mandeville, LA 70471 (985) 629-2082 Phone (985) 629-2110 Fax

HOSE AND PIPELINE TESTS

VESSEL	FMT 3200
X X	* 48
THE FOLLOWING ITEMS B	AVE BEEN CHECKED AND TESTED IN ACCORDANCE WITH SCFR 156.170 ON 7-8-23
	PRESSURE GAUGES HAVE BEEN CHECKED WITHIN 10% OF ACCURACY.
	EMERGENCY SHUTDOWN HAS BEEN CHECKED AND FOUND OPERABLE.
	TRASFER SYSTEM RELIEF VALVE HAS BEEN TESTED AND CHECKED - 125 P.S.I.
* ./	ALL TRANSFER PIPING SYSTEMS AND ASSOCIATED VALVES HAVE BEEN TESTED AND CHECKED AT 187.5 P.S.I.
- N	CARGO HOSE VISUALLY AND HYDROSTATICALLY CHECKED TO 225 P.S.I.
	· ·
THE ABOVE ITEMS CHECK	CED, TESTED AND VERIFIED BY:

Florida Marine Transporters Inc.

MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BB-NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER OPERATIONS SECTION 61.00-61.306

VESSEL: FMT 3200	OFFICIAL NUMBER: 120 1029
TESTING LOCATION: ARTO FLT. U ACA.	MAXIMUM LOADING RATE (BPH) 5,000
VESSEL OWNER AND ADDRESS: FWT 236	PRESSURE INDICATOR: MANDEUILLE
TES	T RESULTS
TEST DATE: (-8- 45	and the second of the second o
TEST DATE: 7-9-23 BEGINNING PRESSURE: 28" of 42° ENDING PRESSURE: 28" of 42°	BEGINNING TIME: 1400
ENDING PRESSURE: 28 "0 = 120	ENDING TIME: 1730
TOTAL PRESSURE LOSS:O	
NOTE: VESSEL IS CONSIDERED VAPOR TIGHT IF "TO	TAL PRESSURE LOSS" IS LESS THAN "ALLOWABLE PRESSURE LOSS"
	•
	CCORDANCE WITH SECTION 61.304F, AND IS
	RED VAPOR TIGHT.
TESTER: CARPY HIC (PRINT)	WITNESS: Stevasile (PRINT) WITNESS: (SIGN)
TESTER: (SIGN)	WITNESS: (SIGN)
	FMT
	AFFILIATION OF WITNESS
CALCULATION OF ALLOWABLE PRESSURE LOSS:	
1861 × 15.7 ×1 5000 1 30	706)= 2.2
0.861 x /5.7 x (5,000 / 30 (L)	(V) (APL)
TP = 14.7 PLUS THE BARGE TEST PRESSURE IN PSI (L = MAXIMUM LOADING RATE IN BARRELS PER F V = VOLUME OF TANK(S) IN BARRELS APL = ALLOWABLE PRESSURE LOSS IN INCHES OF	HOUR
NOTES: 14.70psi = 406.8 inches of H2O	
1psi = 27.67 inches of H2O	
1 inch = 25.40 mm	×
1inch = 2.54 cm	
1oz. = 1.729 inches OF H2O	