

Florida Marine Transporters, Inc.

2360 Fifth Street Mandeville, LA 70471 (985) 629-2082 Phone (985) 629-2110 Fax

HOSE AND PIPELINE TESTS

| VESSEL; | Furt 3242 | | |
|--|--|----|--|
| THE FOLLOWING ITEMS HA CFR 35.35-70 AND 33 CFR 1 | AVE BEEN CHECKED AND TESTED IN ACCORDANCE WITH A 156.170 ON | 16 | |
| PI | RESSURE GAUGES HAVE BEEN CHECKED | | |
| | ITHIN 10% OF ACCURACY. MERGENCY SHUTDOWN HAS BEEN CHECKED ND FOUND OPERABLE. | | |
| TF | RANSFER SYSTEM RELIEF VALVE HAS BEEN STED AND CHECKED ~ 125 P.S.I | | |
| AL AS | LL TRANSFER PIPING SYSTEMS AND SOCIATED VALVES HAVE BEEN TESTED AND | | |
| N/H CA | ARGO HOSE VISUALLY AND PROSTATICALLY CHECKED TO 225 P.S.I. | | |
| VA | APOR PIPELINE HAS BEEN VISUALLY RECKED AND IS CLEAR OF POLMERIZING | | |
| THE ABOVE | ITEMS CHECKED, TESTED, AND VERIFIED BY: | | |
| TOTAL TIME OF THE OFFICE OF TH | | | |



Florida Marine Transporters, Inc.

2360 Fifth Street Mandeville, LA 70471 (985) 629-2082 Phone (985) 629-2110 Fax

MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BB-NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER OPERATIONS SECTION 61.00-61.306

| VESSEL FM+ 3242 | OFFICIAL NUMBER: 1239324 | |
|--|--|--|
| TESTING LOCATION: Fmt Shipyard | MAXIMUM LOADING RATE (BPH) 5,000 | |
| | PRESSURE INDICATOR: MANometer | |
| VESSEL OWNER AND ADDRESS: FMT Industri | es LLC/ 2360 FiFm St. Mandeville, LA 70411 | |
| TEST DATE: 5/14/22 | RESULTS | |
| BEGINNING PRESSURE: 28 ° of Has | BEGINNING TIME: (0:00 am | |
| ending pressure: 28" of H20 | ENDING TIME: // 00 am | |
| TOTAL PRESSURE LOSS: | ALLOWABLE PRESSURE LOSS: 2.2"./ 1/20 | |
| NOTEL PESSEL IS CONSIDERED PAPOR TIGHT IF STOTAL PRESSURE LOSS" IS LESS THAN "ALLOWABLE PRESSURE LOSS" | | |
| THIS VESSEL HAS BEEN TESTED IN ACCORDANCE WITH SECTION 61.304F, AND IS CONSIDERED VAPOR TIGHT. | | |
| TESTER: (PRINT) | WITNESS: Adam Brand (PRINT) | |
| TESTER: (SIGN) | WITNESS: (SIGN) | |
| | Barge Rop AMT AFFILIATION OF WITNESS | |
| CALCULATION OF ALLOWABLE PRESSURE LOSS: | | |
| 0.861 × 15.7 × (5.000 / 30, (V) | $\frac{7.06}{(APL)} = \frac{2.2}{(APL)}$ | |
| TP = 14.7 PLUS THE BARGE TEST PRESSURE IN PSI (I L = MAXIMUM LOADING RATE IN BARRELS PER HO V = VOLUME OF TANK(S) IN BARRELS APL = ALLOWABLE PRESSURE LOSS IN INCHES OF W | DUR | |
| NOTES: 14.70psi = 406.8 inches of H2O 1psi = 27.67 inches of H2O 1 inch = 25.40 mm linch = 2.54 cm 1oz. = 1.729 inches OF H2O | | |