2360 Fifth Street Mandeville, LA 70471 (985) 629-2082 Phone (985) 629-2110 Fax

HOSE AND PIPELINE TESTS

FMT 3246
CHECKED AND TESTED IN ACCORDANCE WITH 170 ON 12-18-23
PRESSURE GAUGES HAVE BEEN CHECKED WITHIN 10% OF ACCURACY.
EMERGENCY SHUTDOWN HAS BEEN CHECKED AND FOUND OPERABLE.
TRASFER SYSTEM RELIEF VALVE HAS BEEN TESTED AND CHECKED - 125 P.S.I.
ALL TRANSFER PIPING SYSTEMS AND ASSOCIATED VALVES HAVE BEEN TESTED AND CHECKED AT 187.5 P.S.I.
CARGO HOSE VISUALLY AND HYDROSTATICALLY CHECKED TO 225 P.S.I.
A augus Foruces
1

Florida Marine Transporters Inc.

MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

	THE PARTY PA
ı	REQUIRED SUBPART BB-NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER OPERATIONS SECTION 61.00-61.306
3	VESSEL: FMT 3246 OFFICIAL NUMBER: 1240862
	VESSEL! 5 000
	TESTING LOCATION: STS FLT. MAXIMUM LOADING RATE (BPH) 5,000
	TANK(S) TESTED: ALL PRESSURE INDICATOR: MANGETER
	VESSEL OWNER AND ADDRESS: FLORIDA MARINE 2360 FIFTH ST. WANDSUILL
	TEST DATE: 12-18-23 TEST RESULTS
	BEGINNING TIME: 1400
è	ENDING TIME: 1900
	TOTAL PRESSURE LOSS: 0 ALLOWABLE PRESSURE LOSS: 2.2 OF #20
	AND AND AND AND PARTY OF THE PROPERTY OF THE P
	NOTE: VESSEL IS CONSIDERED VAPOR TIGHT IF "TOTAL PRESSURE LOSS" IS LESS THAN "ALLOWABLE PRESSURE LOSS"
	THIS VESSEL HAS BEEN TESTED IN ACCORDANCE WITH SECTION 61.304F, AND IS
	CONSIDERED VAPOR TIGHT.
	D'ANDRE CORWARD PRINTO WITNESS: ERIC BRUMFIELD (PRINT)
T	ESTER: D'ANDRE FORWARD (PRINT) WITNESS: ERIC BRUMFIELD (PRINT) HISTER: Muslu Frugal (SIGN) WITNESS: ENT Bumfield (SIGN)
Į,	FATT
	AFFILIATION OF WITNESS
C	ALCULATION OF ALLOWABLE PRESSURE LOSS:
0.	$861 \times \frac{15.7}{\text{(IP)}} \times (\frac{5,000}{\text{(L)}}) = \frac{2.2}{\text{(APL)}}$
T L V A	P = 14.7 PLUS THE BARGE TEST PRESSURE IN PSI (1psi = 16 ounces) = MAXIMUM LOADING RATE IN BARRELS PER HOUR = VOLUME OF TANK(5) IN BARRELS PL = ALLOWABLE PRESSURE LOSS IN INCHES OF WATER NOTES: i4.70psi = 406.8 inches of H20 ipsi = 27.67 inches of H20 i inch = 25.40 mm inch = 2.54 cm loz. = 1.729 inches OF H20