

2360 Fifth Street Mandeville, LA 70471 (985) 629-2082 Phone (985) 629-2110 Fax

HOSE AND PIPELINE TESTS

VESSEL:	MT 3300
THE FOLLOWING ITEMS HAVE BEEN CHECKED AND TESTED IN ACCORDANCE WITH 46CFR 35.35-70 AND 33CFR 156.170 ON 675-23.	
	PRESSURE GAUGES HAVE BEEN CHECKED WITHIN 10% OF ACCURACY.
	EMERGENCY SHUTDOWN HAS BEEN CHECKED AND FOUND OPERABLE.
	TRASFER SYSTEM RELIEF VALVE HAS BEEN TESTED AND CHECKED - 125, P.S.I.
	ALL TRANSFER PIPING SYSTEMS AND ASSOCIATED VALVES HAVE BEEN TESTED AND CHECKED AT 187.5 P.S.I.
- /A	CARGO HOSE VISUALLY AND HYDROSTATICALLY CHECKED TO 225 P.S.I.
THE ABOVE ITEMS CHECKED, TEST	ED AND VERIFIED BY:
×	Lechyon

MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BB-NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER OPERATIONS SECTION 61.00-61.306 129 4601 YESSEL: FMT 3300 OFFICIAL NUMBER: TESTING LOCATION: DEVOLL FLT L, C, MAXIMUM LOADING RATE (BPH) 5,000 PRESSURE INDICATOR: MANGETER TANK(S) TESTED: A22 VESSEL OWNER AND ADDRESS: FMT 2360 FIFTH ST TEST RESULTS 6-15-23 BEGINNING PRESSURE: 28" OF 420 BEGINNING TIME: ENDING PRESSURE: 4810F H20 ENDING TIME: _ ALLOWABLE PRESSURE LOSS: 2.2". 1/20 TOTAL PRESSURE LOSS: NOTE: VESSEL IS CONSIDERED VAPOR TIGHT IF "TOTAL PRESSURE LOSS" IS LESS THAN "ALLOWABLE PRESSURE LOSS" THIS VESSEL HAS BEEN TESTED IN ACCORDANCE WITH SECTION 61.304F, AND IS CONSIDERED VAPOR TIGHT. (PRINT) CHAMPAGNE (PRINT) WITNESS: (SIGN) FLORIDA MARINE AFFILIATION OF WITNESS CALCULATION OF ALLOWABLE PRESSURE LOSS: $(V) = \frac{2.2}{(APL)}$ TP = 14.7 PLUS THE BARGE TEST PRESSURE IN PSI (1psi = 16 ounces) L = MAXIMUM LOADING RATE IN BARRELS PER HOUR V = VOLUME OF TANK(S) IN BARRELSAPL = ALLOWABLE PRESSURE LOSS IN INCHES OF WATER 14.70psi = 406.8 inches of H2O NOTES: 1psi = 27.67 inches of H2O 1 inch = 25.40 mmlinch = 2.54 cmloz. = 1.729 inches OF H2O