

2360 Fifth Street Mandeville, LA 70471 (985) 629-2082 Phone (985) 629-2110 Fax

## HOSE AND PIPELINE TESTS

VESSEL: FMT 5072	
THE FOLLOWING ITEMS HAVE BEEN CHECKED AND TESTED IN ACCORDANCE WITH 46CFR 35.35-70 AND 33CFR 156.170 ON 6-11-23.	
	PRESSURE GAUGES HAVE BEEN CHECKED WITHIN 10% OF ACCURACY.
	EMERGENCY SHUTDOWN HAS BEEN CHECKED AND FOUND OPERABLE.
	TRASFER SYSTEM RELIEF VALVE HAS BEEN TESTED AND CHECKED - 125 P.S.I.
N/A	ALL TRANSFER PIPING SYSTEMS AND ASSOCIATED VALVES HAVE BEEN TESTED AND CHECKED AT 187.5 P.S.I.
<i>P</i> / <i>A</i>	CARGO HOSE VISUALLY AND HYDROSTATICALLY CHECKED TO 225 P.S.I.
THE ABOVE ITEMS CHECKED, TESTED AND VERIFIED BY:	

Florida Marine Transporters Inc.

## MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BB-NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER OPERATIONS SECTION 61.00-61.306 FMT 5072 OFFICIAL NUMBER:\_ TESTING LOCATION: BUICHALO MAR FLANAMUM LOADING RATE (BPH) 5,000 PRESSURE INDICATOR: MANONETER TANK(S) TESTED: ALL VESSEL OWNER AND ADDRESS: FMT 2360 FIFTH TEST RESULTS TEST DATE: 6-11-0 BEGINNING TIME: 1430 BEGINNING PRESSURE: 23" of As 8 ENDING PRESSURE: 28 109 H ENDING TIME: ALLOWABLE PRESSURE LOSS: 2.2". FH20 TOTAL PRESSURE LOSS: NOTE: PESSEL IS CONSIDERED PAPOR TIGHT IF TOTAL PRESSURE LOSS" IS LESS THAN "ALLOWABLE PRESSURE LOSS" THIS VESSEL HAS BEEN TESTED IN ACCORDANCE WITH SECTION 61.304F, AND IS CONSIDERED VAPOR TIGHT. CHAMPAGNE (PRINT) WITNESS: US (SIGN) \_\_\_\_ (SIGN) LORIDA MARINE AFFILIATION OF WITNESS CALCULATION OF ALLOWABLE PRESSURE LOSS: TP = 14.7 PLUS THE BARGE TEST PRESSURE IN PSI (1psi = 16 ounces) L = MAXIMUM LOADING RATE IN BARRELS PER HOUR v = volume of tank(s) in barrelsAPL = ALLOWABLE PRESSURE LOSS IN INCHES OF WATER  $14.70 \text{psi} = 406.8 \text{ inches of } \text{H}_{20}$ NOTES: 1psi = 27.67 inches of H2O 1 inch = 25.40 mmlinch = 2.54 cmloz. = 1.729 inches OF H2O