Florida Marine Transporters, Inc.

2360 Fifth Street Mandeville, LA 70471 (985) 629-2082 Phone (985) 629-2110 Fax

HOSE AND PIPELINE TESTS

	VESSEL:	MT 5074
	5	
THE FOLLOWING ITEMS HAVE BEEN CHECKED AND TESTED IN ACCORDANCE WITH 46CFR 35.35-70 AND 33CFR 156.170 ON $8-27-23$.		
		* · · · · · · · · · · · · · · · · · · ·
		PRESSURE GAUGES HAVE BEEN CHECKED WITHIN 10% OF ACCURACY.
*		EMERGENCY SHUTDOWN HAS BEEN CHECKED AND FOUND OPERABLE.
4.		TRASFER SYSTEM RELIEF VALVE HAS BEEN TESTED AND CHECKED - 125 P.S.I.
		ALL TRANSFER PIPING SYSTEMS AND ASSOCIATED VALVES HAVE BEEN TESTED AND CHECKED AT 187.5 P.S.I.
	W/A	CARGO HOSE VISUALLY AND HYDROSTATICALLY CHECKED TO 225 P.S.I.
*	*	* * * * * * * * * * * * * * * * * * *

THE ABOVE ITEMS CHECKED, TESTED AND YERIFIED BY:

Florida Marine Transporters Inc.

MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BB-NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER OPERATIONS SECTION 61.00-61.306 OFFICIAL NUMBER: TESTING LOCATION: CUMMING FET MAXIMUM LOADING RATE (BPH) TANK(S) TESTED: ____ALL PRESSURE INDICATOR:_ VESSEL OWNER AND ADDRESS: FMT 2360 FIFTH TEST RESULTS BEGINNING PRESSURE: 18 10 F 142 0 BEGINNING TIME: ENDING PRESSURE: ALLOWABLE PRESSURE LOSS: 2.2" . A H20 TOTAL PRESSURE LOSS: NOTE: VESSEL IS CONSIDERED VAPOR TIGHT IF "TOTAL PRESSURE LOSS" IS LESS THAN "ALLOWABLE PRESSURE LOSS" THIS VESSEL HAS BEEN TESTED IN ACCORDANCE WITH SECTION 61.304F, AND IS CONSIDERED VAPOR TIGHT. WITNESS: DAVID ROBERT MCNEMAR (PRINT) (SIGN) (SIGN) AFFILIATION OF WITNESS CALCULATION OF ALLOWABLE PRESSURE LOSS: TP = 14.7 PLUS THE BARGE TEST PRESSURE IN PSI (1psi = 16 ounces) L = MAXIMUM LOADING RATE IN BARRELS PER HOUR V = YOLUME OF TANK(S) IN BARRELS APL = ALLOWABLE PRESSURE LOSS IN INCHES OF WATER 14.70psi = 406.8 inches of H2O NOTES: 1 psi = 27.67 inches of H2O linch = 25.40 mm linch = 2.54 cmloz. = 1.729 inches OF H2O