

2360 Fifth Street Mandeville, LA 70471 (985) 629-2082 Phone (985) 629-2110 Fax

HOSE AND PIPELINE TESTS

VESSEL:	MT 6004
THE FOLLOWING ITEMS HAVE BEEN CHECKED AND TESTED IN ACCORDANCE WITH 46CFR 35.35-70 AND 33CFR 156.170 ON $3-17-24$.	
	PRESSURE GAUGES HAVE BEEN CHECKED WITHIN 10% OF ACCURACY.
	EMERGENCY SHUPDOWN HAS BEEN CHECKED AND FOUND OPERABLE.
	TRASFER SYSTEM RELIEF VALVE HAS BEEN TESTED AND CHECKED - 125 P.S.I.
	ALL TRANSFER PIPING SYSTEMS AND ASSOCIATED VALVES HAVE BEEN TESTED AND CHECKED AT 187.5 P.S.I.
NIA	CARGO HOSE VISUALLY AND HYDROSTATICALLY CHECKED TO 225 P.S.I.
THE ABOVE ITEMS CHECKED, TESTED AND VERIFIED BY:	
and and the desired constraints of a sold as	

loz. = 1.729 inches OF H2O

Florida Marine Transporters Inc.

MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BE-NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER OPERATIONS SECTION 61.00-61.306 OFFICIAL NUMBER: FMT 6004 TESTING LOCATION: RATES FLT MAXIMUM LOADING RATE (BPH) 5,000 PRESSURE INDICATOR: MANGETER VESSEL OWNER AND ADDRESS: PLOPIDA MYRINE 236 FIFTH ST TEST RESULTS TEST DATE: 3-17-24 BEGINNING PRESSURE: 23" of 42 9 BEGINNING TIME:___ ALLOWABLE PRESSURE LOSS: 2.2 ~ H20 TOTAL PRESSURE LOSS: NOTE: PESSEL IS CONSIDERED VAPOR TIGHT IF TOTAL PRESSURE LOSS" IS LESS THAN "ALLOWABLE PRESSURE LOSS" THIS VESSEL HAS BEEN TESTED IN ACCORDANCE WITH SECTION 61.304F, AND IS CONSIDERED VAPOR TIGHT. CHAMPAGNE (PRINT) WITNESS: AFFILIATION OF WITNESS CALCULATION OF ALLOWABLE PRESSURE LOSS: $\frac{15.7}{\text{(TP)}} \times (\frac{5.000}{\text{(L)}} / \frac{30.706}{\text{(V)}}) = \frac{2.2}{\text{(APL)}}$ TP = 14.7 PLUS THE BARGE TEST PRESSURE IN PSI (1psi = 16 ounces) L = MAXIMUM LOADING RATE IN BARRELS PER HOUR V = VOLUME OF TANK(S) IN BARRELSAPL = ALLOWABLE PRESSURE LOSS IN INCHES OF WATER NOTES: 14.70psi = 406.8 inches of H2O lpsi = 27.67 inches of H2O l inch = 25.40 mm linch = 2.54 cm