

2360 Fifth Street Mandeville, LA 70471 (985) 629-2082 Phone (985) 629-2110 Fax

HOSE AND PIPELINE TESTS

VESSEL:	-MT 6006
THE FOLLOWING ITEMS HAVE BEEN 46CFR 35.35-70 AND 33CFR 156.	CHECKED AND TESTED IN ACCORDANCE WITH 170 ON 4-14-23.
	PRESSURE GAUGES HAVE BEEN CHECKED WITHIN 10% OF ACCURACY.
	EMERGENCY SHUFDOWN HAS BEEN CHECKED AND FOUND OPERABLE.
	TRASFER SYSTEM RELIEF VALVE HAS BEEN TESTED AND CHECKED - 125 P.S.I.
~/A	ALL TRANSFER PIPING SYSTEMS AND ASSOCIATED VALVES HAVE BEEN TESTED AND CHECKED AT 187.5 P.S.I.
S	CARGO HOSE VISUALLY AND HYDROSTATICALLY CHECKED TO 225 P.S.I.
THE ABOVE ITEMS CHECKED, TEST	ED AND VERIFIED BY:

Florida Marine Transporters Inc.

MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BB-NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER OPERATIONS SECTION 61.00-61.306

VESSEL: FMT 6006	OFFICIAL NUMBER: 125 4/215
TESTING LOCATION: CATES	MAXIMUM LOADING RATE (BPH) 5,000
TANK(S) TESTED: ALL	PRESSURE INDICATOR: MANINETER
VESSEL OWNER AND ADDRESS: FINT 236	OFIFTH ST. MANDEVILLE
TEST DATE: 6-14-23	RESULTS
BEGINNING PRESSURE: 28" OF HAD	BEGINNING TIME: // 00
ENDING PRESSURE: 28 " OF HOD	ENDING TIME:
TOTAL PRESSURE LOSS:	ALLOWABLE PRESSURE LOSS: 2.2". 1/20
NOTE: VESSEL IS CONSIDERED VAPOR FIGHT IF TOT	AL PRESSURE LOSS" IS LESS THAN "ALLOWABLE PRESSURE LOSS"
THIS VESSEL HAS BEEN TESTED IN ACCONSIDER	CCORDANCE WITH SECTION 61.304F, AND IS ED VAPOR TIGHT.
TESTER: LEE CHAMPAGNE (PRINT) TESTER: LO (SIGN)	PLORIDA MUHICINE
CALCULATION OF ALLOWABLE PRESSURE LOSS:	AFFILIATION OF WITNESS
*	706 1- 22
0.861 x /5.7 x (5,000 / 30 (L)	(V) (APL)
TP = 14.7 PLUS THE BARGE TEST PRESSURE IN PSI (L = MAXIMUM LOADING RATE IN BARRELS PER FOUNDE OF TANK(S) IN BARRELS APL = ALLOWABLE PRESSURE LOSS IN INCHES OF	łouk
NOTES: 14.70psi = 406.8 inches of H2O 1psi = 27.67 inches of H2O 1 inch = 25.40 mm linch = 2.54 cm 1oz. = 1.729 inches OF H2O	