2360 Fifth Street Mandeville, LA 70471 (985) 629-2082 Phone (985) 629-2110 Fax

HOSE AND PIPELINE TESTS

VESSEL:	4FL 417
THE FOLLOWING ITEMS HAVE BEEN 46CFR 35.35-70 AND 33CFR 156	CHECKED AND TESTED IN ACCORDANCE WITH
	PRESSURE GAUGES HAVE BEEN CHECKED WITHIN 10% OF ACCURACY.
	EMERGENCY SHUTDOWN HAS BEEN CHECKED AND FOUND OPERABLE.
	TRASFER SYSTEM RELIEF VALVE HAS BEEN TESTED AND CHECKED - 125 P.S.I.
n//n	ALL TRANSFER PIPING SYSTEMS AND ASSOCIATED VALVES HAVE BEEN TESTED AND CHECKED AT 187.5 P.S.I.
	CARGO HOSE VISUALLY AND HYDROSTATICALLY CHECKED TO 225 P.S.I.
THE ABOVE ITEMS CHECKED, TEST	TED AND VERIFIED BY:

Florida Marine Transporters Inc.

MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BB-NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER OPERATIONS SECTION 61.00-61.306

VESSEL: HFL 417 OFFICIAL NUMBER: 1260813.
TESTING LOCATION: BAHLOW FUT MAXIMUM LOADING RATE (BPH) 5,000
TANK(S) TESTED: ALL PRESSURE INDICATOR: MANORETER
VESSEL OWNER AND ADDRESS: FMT 2360 FIFTH ST. MANDEVILLE
TEST RESULTS
TEST DATE: 4-21
BEGINNING PRESSURE: 28" of 42° BEGINNING TIME: 1300
ENDING PRESSURE: 18" OF 1420 ENDING TIME: 1330
TOTAL PRESSURE LOSS: ALLOWABLE PRESSURE LOSS: 2.2 *** H2***
NOTE: VESSEL IS CONSIDERED VAPOR TIGHT IF "TOTAL PRESSURE LOSS" IS LESS THAN "ALLOWABLE PRESSURE LOSS"
THIS VESSEL HAS BEEN TESTED IN ACCORDANCE WITH SECTION 61.304F, AND IS CONSIDERED VAPOR TIGHT.
TESTER. CARPY HILL (PRINT) WITNESS: Stevasiles (PRINT)
TESTER: CARPY HILL (PRINT) WITNESS: Stevasile (PRINT) TESTER: (SIGN) WITNESS: (SIGN)
TESTER: (SIGN) WITNESS: (SIGN)
TESTER:(SIGN) WITNESS:(SIGN)
TESTER: (SIGN) WITNESS: (SIGN) FMT AFFILIATION OF WITNESS