

2360 Fifth Street Mandeville, LA 70471 (985) 629-2082 Phone (985) 629-2110 Fax

HOSE AND PIPELINE TESTS

VESSEL:	MPX 411
THE FOLLOWING ITEMS HAVE BEEN 46CFR 35.35-70 AND 33CFR 156.	CHECKED AND TESTED IN ACCORDANCE WITH
	PRESSURE GAUGES HAVE BEEN CHECKED WITHIN 10% OF ACCURACY.
	EMERGENCY SHUTDOWN HAS BEEN CHECKED AND FOUND OPERABLE.
	TRASFER SYSTEM RELIEF VALVE HAS BEEN TESTED AND CHECKED - 125 P.S.I.
	ALL TRANSFER PIPING SYSTEMS AND ASSOCIATED VALVES HAVE BEEN TESTED AND CHECKED AT 187.5 P.S.I.
al A	CARGO HOSE VISUALLY AND HYDROSTATICALLY CHECKED TO 225 P.S.I.
THE ABOVE ITEMS CHECKED, TEST	ED AND VESTETED BY-
in the state of th	Tes Dy of

Florida Marine Transporters Inc.

MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BB-NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER OPERATIONS SECTION 61.00-61.306 OFFICIAL NUMBER:____ MP X 411 TESTING LOCATION: BURLALO FLT TY CTY MAXIMUM LOADING RATE (BPH) 5,000 PRESSURE INDICATOR: MANONETER TANK(S) TESTED: ALL VESSEL OWNER AND ADDRESS: FMT 2360 FIFTH ST. TEST RESULTS TEST DATE: 12-24-23 BEGINNING PRESSURE: 28" of 7400 BEGINNING TIME: ENDING PRESSURE: 2811 OF 140 ENDING TIME: ____ ALLOWABLE PRESSURE LOSS: 2.2".1/20 TOTAL PRESSURE LOSS: ________ NOTE: VESSEL IS CONSIDERED VAPOR TIGHT IF "TOTAL PRESSURE LOSS" IS LESS THAN "ALLOWABLE PRESSURE LOSS" THIS VESSEL HAS BEEN TESTED IN ACCORDANCE WITH SECTION 61.304F, AND IS CONSIDERED VAPOR TIGHT. TESTER: LEE CHAMPAGNE (PRINT) WITNESS: (SIGN) ____(SIGN) CORIDA MARINE AFFILIATION OF WITNESS CALCULATION OF ALLOWABLE PRESSURE LOSS: $0.861 \times 15.7 \times (5,000) = 2.2$ (TP) (L) (V) (APL) TP = 14.7 PLUS THE BARGE TEST PRESSURE IN PSI (1psi = 16 ounces) L = MAXIMUM LOADING RATE IN BARRELS PER HOUR V = VOLUME OF TANK(S) IN BARRELSAPL = ALLOWABLE PRESSURE LOSS IN INCHES OF WATER 14.70psi = 406.8 inches of H2O NOTES: 1psi = 27.67 inches of H2O 1 inch = 25.40 mmlinch = 2.54 cm1oz. = 1.729 inches OF H2O