2360 Fifth Street Mandeville, LA 70471 (985) 629-2082 Phone (985) 629-2110 Fax

HOSE AND PIPELINE TESTS

VESSEL:	MPX 426
THE FOLLOWING ITEMS HAVE BEEN 46CFR 35.35-70 AND 33CFR 156.	CHECKED AND TESTED IN ACCORDANCE WITH 170 ON 1-20-24.
	PRESSURE GAUGES HAVE BEEN CHECKED WITHIN 10% OF ACCURACY.
	EMERGENCY SHUTDOWN HAS BEEN CHECKED AND FOUND OPERABLE.
	TRASFER SYSTEM RELIEF VALVE HAS BEEN TESTED AND CHECKED - 125 P.S.I.
4 1	ALL TRANSFER PIPING SYSTEMS AND ASSOCIATED VALVES HAVE BEEN TESTED AND CHECKED AT 187.5 P.S.I.
N/A	CARGO HOSE VISUALLY AND HYDROSTATICALLY CHECKED TO 225 P.S.I.
K	A CONTRACTOR OF THE CONTRACTOR
THE ABOVE ITEMS CHECKED, TEST	ED AND VERIFIED BY:

Florida Marine Transporters Inc.

MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BB-NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER OPERATIONS SECTION 61.00-61.306

VESSEL: MPX 426	OFFICIAL NUMBER: 1313706
TESTING LOCATION: BAYOU FLT	MAXIMUM LOADING RATE (BPH) 5,000
TANK(S) TESTED: ALL	PRESSURE INDICATOR: MANOMETER
VESSEL OWNER AND ADDRESS: FWT 236	O FIFTH ST. MANDEVINCE
TEST DATE:	ALLOWABLE PRESSURE LOSS: 2.2" JH20 OTAL PRESSURE LOSS" IS LESS THAN "ALLOWABLE PRESSURE LOSS" ACCORDANCE WITH SECTION 61.304F, AND IS
TESTER: Styn Soft (PRINT	WITNESS: Chad Tolliver (PRINT) WITNESS: Chad Tolliver (SIGN) FINT AFFILIATION OF WITNESS
CALCULATION OF ALLOWABLE PRESSURE LOSS:	APPILIATION OF WITHESS
0.861 x /5.7 x (5,000 / 3	$\frac{O,706}{(V)} = \frac{2.2}{(APL)}$
TP = 14.7 PLUS THE BARGE TEST PRESSURE IN PS L = MAXIMUM LOADING RATE IN BARRELS PER V = VOLUME OF TANK(S) IN BARRELS APL = ALLOWABLE PRESSURE LOSS IN INCHES OF NOTES: 14.70psi = 406.8 inches of H2O 1 psi = 27.67 inches of H2O 1 inch = 25.40 mm 1 inch = 2.54 cm 1 oz. = 1.729 inches OF H2O	Hour