

2360 Fifth Street Mandeville, LA 70471 (985) 629-2082 Phone (985) 629-2110 Fax

HOSE AND PIPELINE TESTS

vessel:M	PX 428
THE FOLLOWING ITEMS HAVE BEEN CHECKED AND TESTED IN ACCORDANCE WITH 46CFR 35.35-70 AND 33CFR 156.170 ON $8-13-24$	
	PRESSURE GAUGES HAVE BEEN CHECKED WITHIN 10% OF ACCURACY.
	EMERGENCY SHUTDOWN HAS BEEN CHECKED AND FOUND OPERABLE.
	TRASFER SYSTEM RELIEF VALVE HAS BEEN TESTED AND CHECKED - 125 P.S.I.
alla or la	ALL TRANSFER PIPING SYSTEMS AND ASSOCIATED VALVES HAVE BEEN TESTED AND CHECKED AT 187.5 P.S.I.
N (# s	CARGO HOSE VISUALLY AND

THE ABOVE ITEMS CHECKED, TESTED AND VERIFIED BY:

The Dy of

Florida Marine Transporters Inc.

MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BB-NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER OPERATIONS SECTION 61.00-61.306

VESSEL: MPX 428	OFFICIAL NUMBER: 1313 708
TESTING LOCATION: ACCUTEANS FLT. CC	MAXIMUM LOADING RATE (BPH) 5,000
	PRESSURE INDICATOR: MANGETER
VESSEL OWNER AND ADDRESS: FLORIDA MA	RINE 236 FIFTHST MANDEVICE, LA
TEST DATE: 3-13-24	RESULTS
	BEGINNING TIME: 300
201100	ENDINGTIME 1330
_	ALLOWABLE PRESSURE LOSS: 2-2 1/20
THIS VESSEL HAS BEEN TESTED IN ACCONSIDER	CORDANCE WITH SECTION 61.304F, AND IS ED VAPOR TIGHT.
TESTER: LEE CHAMPAGNE (PRINT)	WITNESS: MATT BRAZZEL (PRINT) WITNESS: (SIGN)
TESTER: Ze Clyn (SIGN)	WITNESS: (SIGN)
	FMT
CALCULATION OF ALLOWABLE PRESSURE LOSS:	AFFILIATION OF WITNESS
0.861 x 15.7 x (5,000 / 30, 1) (V	$ \frac{7.96}{(APL)} = \frac{2.2}{(APL)} $
FP = 14.7 PLUS THE BARGE TEST PRESSURE IN PSI (1) L = MAXIMUM LOADING RATE IN BARRELS PER HO V = VOLUME OF TANK(S) IN BARRELS APL = ALLOWABLE PRESSURE LOSS IN INCHES OF W NOTES: 14.70psi = 406.8 inches of H2O 1 psi = 27.67 inches of H2O 1 inch = 25.40 mm 1 inch = 2.54 cm 1 oz. = 1.729 inches OF H2O	OUR THE THE PARTY OF THE PARTY