

Florida Marine Transporters, Inc.

2360 Fifth Street Mandeville, LA 70471 (985) 629-2082 Phone (985) 629-2110 Fax

HOSE AND PIPELINE TESTS

VESSEL: F	MT 1402	
THE FOLLOWING ITEMS HAV CFR 35.35-70 AND 33 CFR 15	/E BEEN CHECKED AND TESTED IN ACCORDA 6.170 ON 8-71-74	NCE WITH 46
	ESSURE GAUGES HAVE BEEN CHECKED HIN 10% OF ACCURACY. ERGENCY SHUTDOWN HAS BEEN CHECKED	
TRA	INSFER SYSTEM RELIEF VALVE HAS BEEN FED AND CHECKED - 125 P.S.I	
CHEC	TRANSFER PIPING SYSTEMS AND DCIATED VALVES HAVE BEEN TESTED AND DKED AT 187.5 P.S.I.	
VAPO	GO HOSE VISUALLY AND COSTATICALLY CHECKED TO 225 P.S.I. OR PIPELINE HAS BEEN VISUALLY	
	KED AND IS CLEAR OF POLMERIZING O. MS CHECKED, TESTED, AND VERIFIED BY:	
-	(let	

Florida Marine Transporters Inc.

MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BB-NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER OPERATIONS SECTION 61.00-61.306

VESSEL: EMT 1402	OFFICIAL NUMBER: 1294902
TESTING LOCATION: FMT Shipyard	MAXIMUM LOADING RATE (BPH) 4, 285
TANK(S) TESTED: A22	PRESSURE INDICATOR: MANIONETER
VESSEL OWNER AND ADDRESS: American Inland W	whe LLC, 3938 N carevay AVD STE 3335 Metairie, LA 70002
TEST DATE 8-21-24	T RESULTS
BEGINNING PRESSURE: 28" # 42 °	BEGINNING TIME: 0700
ENDING PRESSURE: 28 OF Hi O	ENDING TIMEO 800
TOTAL PRESSURE LOSS:	ALLOWABLE PRESSURE LOSS: 4,90 ochio
NOTE: YESSEL IS CONSIDERED VAPOR TIGHT IF TOT.	AL PRESSURE LOSS" IS LESS THAN "ALLOWABLE PRESSURE LOSS"
	CCORDANCE WITH SECTION 61.304F, AND IS ED VAPOR TIGHT. WITNESS: Adam Brand (PRINT) WITNESS: (SIGN) FMT
	AFFILIATION OF WITNESS
CALCULATION OF ALLOWABLE PRESSURE LOSS: 0.861 x 14.7 x 4.285 / 1/, (TP) (L) (V	$\frac{066}{(APL)} = \frac{4.90}{(APL)}$
TP = 14.7 PLUS THE BARGE TEST PRESSURE IN PSI (1) L = MAXIMUM LOADING RATE IN BARRELS PER HO V = VOLUME OF TANK(S) IN BARRELS APL = ALLOWABLE PRESSURE LOSS IN INCHES OF W NOTES: 14.70psi = 406.8 inches of H2O 1 psi = 27.67 inches of H2O 1 inch = 25.40 mm 1 inch = 2.54 cm 1 oz. = 1.729 inches OF H2O	DUR